

Professional tool to regroove truck tyres.



Power : 500W
 Heating regulation : Rotatif switch
 Cables length : 1.75m
 Total weight : 5.5kg
 Handle weight : 0.6kg
 Casing weight : 4.5kg

Our regroovers are provided to regroove the thread of those truck tyres designated "**REGROOVABLE**" or marked with symbol "**U**" on the tyre sidewall.

This device was especially developed for an intensive use.

This operation must only be done by a professional - Please refer the tyre manufacturer's instructions.

CHARACTERISTICS

Heating regulation with a rotative switch.
 5 heat settings.

Handle well seated on the tyre when regrooving due to a wide cutting head.

Tool delivered with e free box of blades and a free regrooving gauge.

Box of 20 blades :

C1 3 - 5 mm	C2 6 - 10 mm	C3 8 - 12 mm	C4 10 - 14 mm	C5 12 - 17 mm
R1 3 - 5 mm	R2 5 - 11 mm	R3 7 - 13 mm	R4 9 - 16 mm	R5 11 - 18 mm

Box of 10 blades :

C6 : 20-28mm

SERVICING / REPAIR

Just sometimes clean the cutting head with a metal brush.

Each part is available as spare part.

1 year warranty.

NORMS

Device compliants with the European electrical standard:

- IEC 60335-1:2001 (incl.corr.1:2002) + A1:2004+A2:2006 (incl.corr.1:2006)
- IEC 60335-2-45:2002+A1:2008.